

FibreFlow™
Indoor Tube Flexibility Point
(ITFP) 4 Port
Product Code 7217



1.0 Design Features

- Manufactured from UL94, V0 rated material.
- IP55 Rated.
- Can accommodate fibreFlow™ tube bundles in the range 1 – 19way 5mm.
- Can be used as an external-internal gas seal unit, straight joint or drop joint.
- Provision of secure long term bend protection.
- Can be retro-fitted.
- Re-enterable.
- Can be readily fixed to walls or cable tray.
- Easy to use and install, no special tools required.

2.0 Application

The fibreFlow™ Indoor Tube Flexibility Point (ITFP) is a branch box capable of manipulating a 19 way tube bundle and routing any combination of tube bundles to three separate ports. Each port is identifiable by means of a recessed name-plate.

3.0 Technical Specification

| | | |
|-------------|------------------------|----------------|
| Materials: | UL94, V0 rated Plastic | |
| Dimensions: | Length | 520 mm (20.5") |
| | Width | 280 mm (11") |
| | Depth | 70 mm (2.8") |

4.0 Installation Instructions

See UK_II_7217 (check with Emtelle for most recent issue).

This data sheet is intended as a guide only. Whilst the information it contains is believed to be correct, Emtelle can take no responsibility for actions taken based on the information contained in this document. Emtelle reserves the right to make changes to this document without notice. All sales of product are subject to Emtelle's terms and conditions of sale only, which can be found on Emtelle's website. This document is protected by copyright (c) Emtelle UK Limited [2005]. The products depicted are protected by intellectual property rights. Any unauthorized copying of this document or of our products is prohibited and Emtelle UK Limited will take action to prevent any infringement of its rights and to claim damages for the loss that it suffers.

www.emtelle.com

UK_DS_7217