

UK DS Indoor 4-16F x 1 SM G.657B3 250u

FibreFast

Indoor LSZH Cable 4-16F (2mm)

Product Description

An Indoor rated cable design suitable for installation in buildings. The cable complies with CPR requirements, making it suitable for use in riser spaces and other indoor pathways where fire safety is a priority.

This cable design is ideal for horizontal discreet cable installations.

Cable Performance Standards IEC 60793-1, IEC 60793-2, IEC 60794-2

Cable CPR rating Cca-s1a,d1,a1

Marking and Identification

Cable Cross section:



- Optical Fibre in centre 4-16 fibres
- Aramid Yarn
- Outer sheath LSZH

Fibre colour:

according to EIA 598.



1 Blue 2 Orange 3 Green 4 Brown 5 Grey 6 White 7 Red 8 Black 9 Yellow 10 Violet 11 Pink 12 Aqua

Fibres 13-16 ring marked

Sheath colour:

Cable sheath is white

Cable Marking:

The outer sheath is marked in one meter intervals.

Emtelle FibreFast – Year/week – Fibre Count, Fibre Type – Product Code – Batch ID – Meter Mark

UK DS Indoor 4-16F x 1 SM G.657B3 250u

Specifications

Technical:

Fibre Count	4-16F			
Number of Fibres/Tube	4f	8f	12f	16f
Outer Sheath	low smoke zero halogen (LSZH)			
Cable Diameter – Ø (± 0.5 mm)	2.0 mm			
Peripheral Strength Member	Aramid Yarns			
Cable Weight (± 20% kg /km)	3.1 kg/km	3.4 kg/km	3.7 kg/km	4.0 kg/km
Minimum Bending Radius	10D			
Temperature Range	Transport & Storage		-20°C → +60°C	
	Installation		-10°C → +60°C	
	Operation		-20°C → +60°C	

Performance:

Test	Standard	Specified Value
Tensile Performance	IEC 60794-1-21-E1	100N
Crush	IEC 60794-1-21-E3	500 N/100 mm
Impact	IEC 60794-1-21-E4	1 N.m
Torsion	IEC 60794-1-21-E7	±180°
Temperature Cycling	IEC 60794-1-22-F1	-20 °C to +60 °C
Minimum Bend Radius	IEC-60794-1-21-E11	10xD

Optical Parameters:

Fibre Type	G.657B3		
Attenuation	1310 nm	≤ 0.40 dB/km	
	1550 nm	≤ 0.30 dB/km	
MFD	1310 nm	8.2-9.0	
	1550 nm	9.1-10.1	
Bending Induced Attenuation	1 Turn φ 5mm	1550 nm	≤ 0.15 dB
		1625 nm	≤ 0.45 dB
Core-Cladding Concentricity Error	≤ 0.5 µm		
Cladding Diameter	125 ± 0.7 µm		
Cladding Non Circularity	≤ 0.7 %		
Primary Coating Diameter (uncoloured)	242 ± 5 µm		

Packaging and Labelling

All products suitably packaged in recyclable materials and clearly labelled with Emtelle Product Code and Description where possible.

Wooden drums with protection.

END OF SPECIFICATION